

All our totems are available in two basic tactile technologies:

Infrared technology Key Features:

- · Economic solution based on IR frame.
- Dedicated for public administration, corporate and other places with low traffic.
- · Reliable and durable, provided that the sensors are kept clean.
- From 2 to 40 simlultaneous touch point recognition.

Projected Capacitive technology Key Features:

- · Smooth glass front with zero-bezel design.
- · Waterproof and vandalproof ability.
- Dedicated for restaurants, shopping malls and other places with high traffic.
- · 10 and 40 simultaneous touch point recognition.

V-TOTEM models






V-TOTEM **STANDARD**

A classic interactive totem that works best in hotels, town halls and digital signage applications.

Key features:

- · LCD in portrait orientation with 24/7 operational time
- · IR or PCAP touch screen technology
- · Personalized steel case painted in any RAL color
- · Your company's logo in the lower part and cut-out in side slats

Graphic personalization enlivens the appearance of a standard totem and makes it more visible in public places paying attention to the visual identity of your brand.








V-LECTERN

A multimedia kiosk in a horizontal orientation with a monitor tilted at the right angle to allow comfortable use for people of different height, as well as disabled people in wheelchairs. This solution is most often used in museums and shopping malls for WayFinder applications.

Key features:

- · Screen in horizontal orientation
- · IR and PCAP touch technologies available
- · Housing customization possible
- · Waterproof front in capacitive technology







V-TOTEM CUSTOM

Products from the CUSTOM group are created on special request according to the concept of the architects or our designers. This broad group of products is most often used in the modern museums, educational and scientific centers and other public facilities. They are characterized by a variety of shapes and high quality finishing materials such as Corian®, stainless steel, Corten steel (rust-coated in a controlled manner) as well as glass and wood. From the early stage we participate in the concept presentation, product visualization as well as executive documentation necessary in public procurements.

For private investors we make more and more popular showroom exhibitions where strong emphasis is placed on the so-called WOW factor. Custom kiosks and totems stand out from the competition, improve the quality of the presented products or services and support sales. Chosing dedicated products, you transform a typical presentation and sales process into an unforgettable experience which stays in the heads of your clients for a long time.



Ultra HD



24/7



Horizontal orientation



Multi-touch up to 40 points



Toughened vandalproof glass



Antiglare coating



Any RAL color



Branding










V-TOTEM OUTDOOR


An interactive totem created especially for working outside in the most demanding weather conditions.

Key features:

- · Reinforced construction and safety glass makes OUTDOOR totem resistant to vandalism
- · Special sealing, heating and ventilation system
- · High brightness monitor almost 10 times brighter than regular one with special sun-protective filter
- · Capacitive touch screen capable to work through glass with thickness up to 12 mm
- · Personalized enclosure







| | | V-TOTEM 32 PCAP10 V-LECTERN 32 PCAP10 | V-TOTEM 43 PCAP10 V-LECTERN 43 PCAP10 | V-TOTEM 49 PCAP10 V-LECTERN 49 PCAP10 | V-TOTEM 55 PCAP10 V-LECTERN 55 PCAP10 | V-TOTEM 65 PCAP10 V-LECTERN 65 PCAP10 | | |
|----------------------------|--|---|--|--|--|--|--|--|
| | Diagonal | 32" | 43" | 49" | 55" | 65" | | |
| | Resolution | 1920 x 1080 (Full HD) | 1920 x 1080 (Full HD) | 3840 x 2160 (Ultra HD) | 3840 x 2160 (Ultra HD) | 3840 x 2160 (Ultra HD) | | |
| | Aspect ratio | 16:9 | 16:9 | 16:9 | 16:9 | 16:9 | | |
| LCD | Brightness | 350 cd/m ² | 350 cd/m ² | 500 cd/m ² | 500 cd/m ² | 500 cd/m ² | | |
| LCD | Contrast | 1100:1 | 1100:1 | 1100:1 | 1100:1 | 1100:1 | | |
| | Operational time | 18/7 | 18/7 | 24/7 | 24/7 | 24/7 | | |
| | Viewing angles | 178° / 178° | 178° / 178° | 178° / 178° | 178° / 178° | 178° / 178° | | |
| | Orientation | Portrait / Landscape | | | | | | |
| | Touch technology | Projected Capacitive Touch | | | | | | |
| | Number of touch points | 10 | | | | | | |
| | Glass | Toughened glass with antiglare coating | | | | | | |
| | Touch detection | Finger, gloved hand or conductive stylus | | | | | | |
| TOUCH SCREEN | Touch Pressure | <0.1g | | | | | | |
| SCILCEIN | Minimum object size | 8 mm for finger, 3 mm for conductive stylus | | | | | | |
| | Response time | 5-16 ms | | | | | | |
| | Compatible operating systems | Windows 7/8/10 - HID plug & play, Linux, Android, MAC - driver required | | | | | | |
| | Touch accuracy | ± 1,5 mm | | | | | | |
| | Processor | Intel® Core™ i3 / i5 / i7 | | | | | | |
| | RAM | 4 GB / 8 GB / 16 GB | | | | | | |
| PC | HDD | SSD 64 GB / 128 GB / 256 GB | | | | | | |
| PL | Graphic card | Zintegrowana | | | | | | |
| | Communication | LAN (RJ-45), WiFi | | | | | | |
| | Operating system | Windows 10 PRO | | | | | | |
| | Enclosure | Free standing or wall mounted option | | | | | | |
| CONSTRUCTION | Color | any RAL color | | | | | | |
| CONSTRUCTION | Personalize option | YES | | | | | | |
| | Service access | Back (front access available upon request) | | | | | | |
| | Speakers | YES | | | | | | |
| | Webcam | YES | | | | | | |
| ODTIONAL | External input/output panel (USB, LAN, HDMI, Jack) | YES | | | | | | |
| OPTIONAL ACCESSORIES | NFC | YES | | | | | | |
| | Card dispenser | YES | | | | | | |
| | Printer | YES | | | | | | |
| | Barcode/QR code reader | YES | | | | | | |
| | Operational temperature | | | 0°C - 50°C | | | | |
| | Operational humidity | 10% - 80% | | | | | | |
| Warranty 3 years with exte | | | | | rs | | | |

V-TOTEM / V-LECTERN with infrared touch specification

| Processor Proc | | | V-TOTEM 32 IR10 V-LECTERN 32 IR10 | V-TOTEM 43 IR10 V-LECTERN 43 IR10 | V-TOTEM 49 IR10 V-LECTERN 49 IR10 | V-TOTEM 55 IR10 V-LECTERN 55 IR10 | V-TOTEM 65 IR10 V-LECTERN 65 IR10 | | |
|--|--------------|--|---|--------------------------------------|--------------------------------------|--------------------------------------|--------------------------------------|--|--|
| Page | | Diagonal | 32" | 43" | 49" | 55" | 65" | | |
| Registrace | | Resolution | 1920 x 1080 (Full HD) | 1920 x 1080 (Full HD) | 3840 x 2160 (Ultra HD) | 3840 x 2160 (Ultra HD) | 3840 x 2160 (Ultra HD) | | |
| Control 1001 1003 | | Aspect ratio | 16:9 | 16:9 | 16:9 | 16:9 | 16:9 | | |
| Contract | LCD | Brightness | 350 cd/m ² | 350 cd/m ² | 500 cd/m ² | 500 cd/m ² | 500 cd/m ² | | |
| Viewing engles | LCD | Contrast | 1100:1 | 1100:1 | 1100:1 | 1100:1 | 1100:1 | | |
| Control Cont | | Operational time | 18/7 | 18/7 | 24/7 | 24/7 | 24/7 | | |
| Number of touch pointed Number of touch obtacked Name object Number of touch obtacked Number of touch object of touch obtacked Number of touch object | | Viewing angles | 178° / 178° | 178° / 178° | 178° / 178° | 178° / 178° | 178° / 178° | | |
| Function Function | | Orientation | Portrait / Landscape | | | | | | |
| TOUCH Touch desertion Touch desertion Any edject | | Touch technology | | | | | | | |
| TOUCH TOUCH Pressure Touch detection Touch Pressure Touch Pressure Touch Pressure Touch Pressure Touch Pressure Touch pressure required Touch pressure Touch pressure Touch pressure Touch pressure Touch pressure Touch pressure Touch parties Touch partie | | Number of touch points | 2/10/16/40 | | | | | | |
| Touch Pressure Touch Eccaracy Touch Accuracy Touc | | Glass | Toughened glass with antiglare coating | | | | | | |
| SCREEN Touch Pressure RESPORTED 1 Response time Response time Minimum objects size Touch accuracy Ompatible operating system Sampling frequency to the accuracy BAM 4 GB // B GB // 16 GB HOD 5505 6x GB // 126 GB // 256 GB HOD 5505 6x GB // 126 GB // 256 GB Graphic card 1 Integrated CONSTRUCTION Finctiosure Finctiosure Fi | | Touch detection | | | | | | | |
| Minimum object size Smm Response time | | Touch Pressure | | | | | | | |
| Compatible operating systems | SCILCEIA | Minimum object size | | | | | | | |
| Touch accuracy | | Response time | | | | | | | |
| Processor Intel® Core 3 / 15 / 17 | | Compatible operating systems | Windows 7/8/10 - HID plug & play, Linux, Android, MAC - driver required | | | | | | |
| PC RAM 4 GB / B GB / 16 GB PC HDD 550 64 GB / 126 GB HDD 550 64 GB / 126 GB Graphic card Integrated COmmunication LAN (RJ-45), WFI Operating system Windows 10 PRO CONSTRUCTION Color any RAL color Personalize option YES Service access Back (front access available upon request) ACCESSORIES Webcam YES Mebcam YES MEC YES ACCESSORIES NFC YES PRINTER YES Bacrode/QR code reader YES Bacrode/QR code reader YES Operational temperature Operational temperature O'C - 50°C | | Touch accuracy | | | | | | | |
| PC RAM 4 6B / 8 GB / 126 GB HDD \$50 64 GB / 128 GB / 256 GB Graphic card Integrated COMSTRUCTION Operating system Windows ID PRO CONSTRUCTION Enclosure Free standing or wall mounted option CONSTRUCTION Personalize option YES Service access Back (front access available upon request) ACCESSORIES Webcam YES VES VES Card dispenser YES Card dispenser YES Barcode/QR code reader YES Barcode/QR code reader YES | | Sampling frequency | up to 450 fps | | | | | | |
| PC HDD 55D 64 6B / 128 GB / 256 GB Graphic card Integrated Communication LAN (RJ-45), WIFI CONSTRUCTION Fendasure Windows 1D PRO CONSTRUCTION Color any RAL color Personalize option YES Service access Back (front access available upon request) ACCESSORIES YES VES Webcam YES ACCESSORIES YES Card dispenser YES Forinter YES Barcode/QR code reader YES Barcode/QR code reader YES Operational temperature O'C-50°C | | Processor | Intel® Core™ i3 / i5 / i7 | | | | | | |
| PC Graphic card Integrated COMMUNICATION LAN (RJ-45), WIF I CONSTRUCTION Operating system Windows ID PRO CONSTRUCTION Fee Enclosure Free standing or wall mounted option CONSTRUCTION Personalize option YES Service access Back (front access available upon request) Speakers YES Webcam YES External input/output panet (USB, LAN, HDMI, Jack) YES NFC YES Card dispenser YES Printer YES Barcode/QR code reader YES Operating system YES | DC. | RAM | 4 GB / 8 GB / 16 GB | | | | | | |
| Communication Communicatio | | HDD | SSD 64 GB / 128 GB / 256 GB | | | | | | |
| CONSTRUCTION Enclosure Windows 10 PRO CONSTRUCTION Enclosure free standing or wall mounted option Color any RAL color Personalize option YES Service access Back (front access available upon request) ACCESSORIES Webcam NFC YES NFC YES Card dispenser YES Printer YES Barcode/QR code reader YES Operational temperature O'C - 50°C | PC | Graphic card | Integrated | | | | | | |
| CONSTRUCTION Enclosure free standing or wall mounted option Personalize option YES Service access Back (front access available upon request) PERSONAL ACCESSORIES VES Webcam YES NEC YES Card dispenser YES Printer YES Barcode/QR code reader YES Operational temperature O'C-50°C | | Communication | LAN (RJ-45), WiFi | | | | | | |
| CONSTRUCTION Personalize option YES Back (front access available upon request) PAPPIONAL ACCESSORIES YES ACCESSORIES NFC YES NFC YES Card dispenser YES Printer YES Barcode/QR code reader YES Operational temperature Operational temperature OPC - 50°C | | Operating system | Windows 10 PRO | | | | | | |
| Personalize option Service access Service access Service access Service access Back (front access available upon request) YES Webcam YES Webcam YES External input/output panel (USB, LAN, HDMI, Jack) NFC Card dispenser YES Card dispenser YES Printer Barcode/QR code reader Operational temperature Operational temperature | | Enclosure | free standing or wall mounted option | | | | | | |
| Personalize option Service access Back (front access available upon request) YES Webcam YES Webcam YES External input/output panel (USB, LAN, HDMI, Jack) NFC Card dispenser Printer Barcode/QR code reader Operational temperature Operational temperature | CONSTRUCTION | Color | any RAL color | | | | | | |
| Speakers Webcam YES Webcam YES External input/output panel (USB, LAN, HDMI, Jack) NFC NFC Card dispenser YES Card dispenser YES Barcode/QR code reader Operational temperature Operational temperature | CONSTRUCTION | Personalize option | YES | | | | | | |
| Webcam PTIONAL ACCESSORIES External input/output panel (USB, LAN, HDMI, Jack) NFC Card dispenser Printer Printer Barcode/QR code reader Operational temperature Operational temperature | | Service access | Back (front access available upon request) | | | | | | |
| PTIONAL ACCESSORIES NFC Card dispenser Printer Barcode/QR code reader Operational temperature External input/output panel (USB, LAN, HDMI, Jack) YES YES YES YES Operational temperature | | Speakers | YES | | | | | | |
| NFC ACCESSORIES NFC Card dispenser Printer Barcode/QR code reader Operational temperature YES YES YES OPC - 50°C | | Webcam | YES | | | | | | |
| ACCESSORIES NFC Card dispenser Printer Barcode/QR code reader Operational temperature NFC YES YES YES YES OPES YES YES YES YES | ODTIONAL | External input/output panel (USB, LAN, HDMI, Jack) | YES | | | | | | |
| Printer Barcode/QR code reader Operational temperature YES O°C - 50°C | | NFC | YES | | | | | | |
| Barcode/QR code reader Operational temperature YES O°C - 50°C | | Card dispenser | YES | | | | | | |
| Operational temperature 0°C - 50°C | | Printer | YES | | | | | | |
| орениями интречине | | Barcode/QR code reader | YES | | | | | | |
| | | Operational temperature | | | 0°C - 50°C | | | | |
| Operational humidity 10% - 80% | | Operational humidity | 10% - 80% | | | | | | |
| Warranty 3 years with extension option up to 5 years | | Warranty | 3 years with extension option up to 5 years | | | | | | |

| | | V-TOTEM 32 OUTDOOR | V-TOTEM 49 OUTDOOR | V-TOTEM 55 OUTDOOR | V-TOTEM 75 OUTDOOR | |
|-----------------|--|---|------------------------|------------------------------------|------------------------|--|
| | Diagonal | 32" | 49" | 55" | 75" | |
| | Resolution | 1920 x 1080 (Full HD) | 1920 x 1080 (Full HD) | 1920 x 1080 (Full HD) | 3840 x 2160 (Ultra HD) | |
| | Aspect ratio | 16:9 | 16:9 | 16:9 | 16:9 | |
| LCD | Brightness | 2500 cd/m ² | 3000 cd/m ² | 3000 cd/m ² | 3000 cd/m ² | |
| LCD | Contrast | 1300:1 | 1300:1 | 1000:1 | 1200:1 | |
| | Operational time | 24/7 | 24/7 | 24/7 | 24/7 | |
| | Viewing angles | 178° / 178° | 178° / 178° | 178° / 178° | 178° / 178° | |
| | Orientation | Portrait / Landscape | | | | |
| | Touch technology | Projected Capacitive Touch | | | | |
| | Number of touch points | 10 | 10 | 10 | 40 | |
| | Glass | Toughened safety glass with Sun-Stop | | n-Stop filter (ESG VSG UVIR 4.4.2) | | |
| TOUGH | Touch detection | Finger, gloved hand or conductive stylus | | | | |
| TOUCH SCREEN | Touch Pressure | h Pressure <0,1 g | | | | |
| Serveer | Minimum object size | 8 mm for finger, 3 mm for conductive stylus | | | | |
| | Response time | 5-16 ms | | | | |
| | Compatible operating systems | Windows 7/8/10 - HID plug & play, Linux, Android, MAC - driver required | | | | |
| | Touch accuracy | ± 1,5 mm | | | | |
| | Processor | Intel® Core™ i3 / i5 / i7 | | | | |
| | RAM | 4 GB / 8 GB / 16 GB | | | | |
| PC | HDD | SSD 64 GB / 128 GB / 256 GB | | | | |
| FC | Graphic card | Integrated with PCB | | | | |
| | Communication | LAN (RJ-45), WiFi | | | | |
| | Operating system | Windows 10 PRO | | | | |
| | Enclosure | Free standing or wall mounted option | | | | |
| CONSTRUCTION | Color | Any RAL color | | | | |
| CONSTRUCTION | Personalize option | YES | | | | |
| | Service access | FRONT | | | | |
| | Speakers | YES | | | | |
| | Webcam | YES | | | | |
| OPTIONAL | External input/output panel (USB, LAN, HDMI, Jack) | NO NO | | | | |
| ACCESSORIES | NFC | YES | | | | |
| | Card dispenser | NO | | | | |
| | Printer | | YES | | | |
| | Barcode/QR code reader | YES | | | | |
| | Operational temperature | -30°C - 50°C | | | | |
| | Operational humidity | 10% - 80% | | | | |
| | Warranty | 3 years with extension option up to 5 years | | | | |